## **Amendments to the Claims:**

If entered, this listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1-12 (cancelled).

13 (previously presented). A ferroelectric material, comprising:

a perovskite alloy comprising stacked planes having the form Pb(Sc<sup>3+</sup><sub>0.5+v</sub>Nb<sup>5+</sup><sub>0.5-v</sub>)O<sub>3</sub> / Pb(Sc<sup>3+</sup><sub>0.5</sub>Nb<sup>5+</sup><sub>0.5</sub>)O<sub>3</sub> / Pb(Sc<sup>3+</sup><sub>0.5</sub>Nb<sup>5+</sup><sub>0.5</sub>)O<sub>3</sub> , wherein Pb represents lead atoms, Sc<sup>3+</sup> represents scandium atoms, Nb<sup>3+</sup> represents niobium atoms and O represents oxygen atoms, and wherein v is a modulated parameter yielding the relative concentration of the Sc<sup>3+</sup> and Nb<sup>3+</sup> atoms in each plane of said alloy, wherein said alloy is ordered along the [001] direction and wherein said modulated parameter v is selected to obtain at a specific temperature dielectric and piezoelectric properties of said alloy that are enhanced over the dielectric and piezoelectric properties of the disordered alloy; and

wherein said specific temperature is selected from any temperature below the Curie temperature of the disordered alloy and above 50K.